



ALUP COMBI II SERIES
BELT DRIVE LUBRICATED ROTARY SCREW

80 Gallon tank is standard
 200, 208, 230 and 460 volt configurations available

MODEL	Combi-07	Combi-10	Combi-15
HP	7.5	10	15
CFM @ 125	31	41	60
CFM @ 150	27	34	53
CFM @ 190	21	31	46
PIPE NPT	3/4"	3/4"	3/4"
SHIP WEIGHT	893	929	949
LIST PRICE	\$7,032	\$7,177	\$7,296
dBa	66	68	69
230/1 adder	\$525	n/a	n/a
460 Volt adder	\$250	\$250	\$250
120 Gal tank adder	\$259	\$259	\$259
200 Volt adder	\$225	\$225	\$225
*Auto tank drain	\$164	\$164	\$164
Base Mount (no tank) deduct	(\$187)	(\$187)	(\$187)

*Solenoid timed drain ships loose and requires 115 Volt power source

STANDARD FEATURES

Low sound enclosure	Particulate and coalescing filters
Cabinet pre-filter	Spin on separator element
Pressurized oil change	Synthetic lubricant
Tri Voltage ODP motor	80 Gallon ASME Code tank
dryer/filters condensate drains	Air cooled aftercooler
Refrigerated Air Dryer	Air Control 1 microprocessor



ALUP COMBI II SERIES
BELT DRIVE LUBRICATED ROTARY SCREW

120 Gallon tank is standard
200, 230 and 460 volt configurations available

MODEL	Combi-20	Combi-25	Combi-30
HP	20	25	30
CFM @ 125	78	101	120
CFM @ 150	72	94	112
CFM @ 190	62	78	98
PIPE NPT	1"	1"	1"
SHIP WEIGHT	1619	1647	1684
LIST PRICE	\$15,687	\$16,167	\$16,958
dBA	66	68	69
460 Volt adder	\$350	\$350	\$350
200 Volt adder	\$325	\$325	\$325
*Auto tank drain	\$164	\$164	\$164
Base Mount (no tank) deduct	(\$270)	(\$270)	(\$270)

STANDARD FEATURES

Low sound enclosure
Cabinet prefilter
Pressurized oil change
Tri Voltage ODP motor
dryer/filters condensate drains
Refrigerated Air Dryer
Wye Delta starting

Particulate and coalescing filters
Spin on separator element
Synthetic lubricant
120 Gallon ASME Code tank
Air cooled after cooler
Air Control 1 microprocessor

FOR LARGER HORSE POWER CONTACT PAINT BOOTH TECHNOLOGIES